HyPanel Plus

Datasheet

New hassle-free smart control panel for your home

The akubela HyPanel Plus, a smart control panel with an Android 10 operating system. The ALL IN ONE design integrates smart intercom, ZigBee gateway and home automation, and is compatible with plentiful ecosystem. Multi-modal interaction can be easily used by the whole family, offering the excellent smart home experience.

At a Glance

- **Excellent performance with Android 10 system**
- **2 touch buttons, suitable for the whole family**
- **4” multi-touch screen with energy saving mode**
- **2-gang switch, replace conventional switch**
- **Smart intercom, ZigBee gateway, home automation ALL IN ONE**
- **Kinds of sensors built-in**



Basic Information

- Model Number: PS52-R2-EU
- Power Supply: 180 ~ 250VAC, 50Hz
- Operation System: Android 10
- RAM/ROM: 1GB/8GB
- Wi-Fi: IEEE802.11 b/g/n, @2.4GHz/5GHz
- Bluetooth: Bluetooth 4.2
- Ethernet Port: 1×RJ45, 10/100Mbps adaptive
- ZigBee: ZigBee 3.0
- Output: 2-gang, 1200W total;
  800W/gang for resistive;
  400W/gang for LED/CFL
- Microphone: Dual microphones, -42dBV
- Speaker: Single speaker, 8Ω/1.5W

Appearance

- Material: metal
- Button: 2 touch button
- Screen: 4” multi-touch screen
- Screen Resolution: 480×480 pixels
- Screen Brightness: 210 cd/㎡

Sensors Built In

- Proximity Sensor: 30 ~ 60cm
- Light Sensor: Low-level lux detection
- Temperature Sensor: ±1℃, range: -10 ~ 55℃
- Humidity Sensor: ±5%, range: 10 ~ 90%RH, without condensation

akubela

10/F, No.56 Guanri Road, Software Park II, Xiamen 361009, China
Tel: +86-592-2133061 Ext: 7694 Fax: +86-592-2133061
Email: sales@akuvox.com Web: www.akubela.com

Working Environment

- Environment: For indoor use only
- Working Humidity: 10 ~ 90%RH, without condensation
- Working Temperature: -10 ~ 55℃
- Storage Temperature: -30 ~ 70℃


Application Scenario

- Villas
- Apartment complexes
- Home automation systems
- Modern interiors


Installation

- Installation: Wall flush mounting
- Flush Mounted Module: EU/UK standard
- Wiring Way: L- + N- wire required


Product Dimension Diagram (mm)




5 BOTTOM VIEW




2 RIGHT VIEW




1 FRONT VIEW



3 LEFT VIEW



4 BACK VIEW



6 TOP VIEW

akubela

10/F, No.56 Guanri Road, Software Park II , Xiamen 361009, China
Tel: +86-592-2133061 Ext: 7694 Fax: +86-592-2133061
Email: sales@akuvox.com Web: www.akubela.com